



<div>DECLARATION OF PERFORMANCE</div> <div>DoP №: 108/17</div> <div>XALKIS S.A.</div> <div>Vasiliko Evias p.c. 34002</div>		<div><div>VAVOULIOTIS • GOUNARIS • MITAKIS</div><div>BRICKS & TILES INDUSTRY S.A.</div></div>
<div></div> <div>15X18X32</div>		<div>Vassiliko Evia ,340 02 – Greece</div> <div>Tel : 2221055080</div> <div>mail: info@xalkis-sa.com</div> <div>https://xalkis-sa.com/en/new-home-en/</div>

1. Unique identification code of the product type: 15X18X32
2. Intended use: Clay bricks for protected masonry, Category II, Low Density
3. Manufacturer : XALKIS S.A.
4. System or systems of assessment and verification of constancy of performance of the construction product : System 4
5. Harmonized products: EN 771-1:2011.
6. Declared performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Dimensions (mm) (lengthxwidthxheight)	327X180X147	EN 771-1:2011
Dimensions and tolerances :		
Tolerance / Range	T1/R1	
Flatness of bed faces / Plane parallelism	NPD	
Configuration	Unit as shown in Figure	
Compressive Strength (N/mm ²)[(⊥ to bed face)]	3	
Voids (%)	61	
Dimensional Stability	NPD	
Bond Strength	Fixed 0.15 N/mm ²	
Active soluble salt content:	NPD (S0)	
Reaction to fire:	A1	
Water absorption:	NPD	
Water vapour diffusion coefficient (μ) :	5/10	
Direct Airborne Sound Insulation :		
Gross dry density	731 kg/m ³	
Net dry density	1860 kg/m ³	
Configuration	as above	
Thermal conductivity (λ10 ,eq,dry, unit)	0.158 W/mK,	
Durability Against Freeze Thaw	NPD	
Dangerous substances:	NPD	

7. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011.

Signed on behalf of the manufacturer:

Gounaris Vasileios
CEO

A handwritten signature in blue ink, appearing to read 'Gounaris Vasileios', is written over a faint, light blue rectangular background.

Vasiliko Evia 30/7/18